


UNDER THE BELL PENDANT LAMP - US VERSION

ISKOS-BERLIN ON THE DESIGN "The Under The Bell Pendant Lamp is more than just a lampshade—when situated over a table or in an open space, the bellshaped light creates its own space within the environment. As such, the design embraces and shelters the people underneath, both in a physical and abstract manner, for an intimate atmosphere. The design is made using up to 41% fibers from recycled plastic bottles that, along with its unique shape, enables the Under The Bell pendant lamp to have an impact on the acoustics of a room."






CEILING CAP




3,5 cm / I.5"

Ø II cm / 4.25"

Ø 55 CM/21.7"



Ø 82 CM/32.25



DESIGNED BY / YEAR OF DESIGN

Iskos-Berlin / 2011

ABOUT THE DESIGNER

Iskos-Berlin is a Copenhagen-based design duo that has made International headlines within furniture, industrial and graphic design. The studio, formerly known as Komplot Design has collaborated with some of the World's most prestigious manufacturers and their furniture, lighting and other design products are exhibited at numerous design museums around the World including MoMA and the Designmuseum Denmark.

CATEGORY

Pendant lamp

ENVIRONMENT

Indoor

COUNTRY OF PRODUCTION

Germany

DESCRIPTION

Designed in a material that uses up to 418 fibers from recycled plastic bottles, the Under The Bell Pendant Lamp not only brings a tactile and modern expression to any space but also impacts the acoustics of a room through its soft shade, paired with its graphic lines and subtle color palette.

PRODUCTION PROCESS

Large sheet of PET material is heated in a mould and pressed into its shape.

MATERIAL

Shade made using up to 418 fibers from recycled plastic bottles. Rubber cord.

CORD LENGTH

500 cm / 197"

BULB INCLUDED

CEILING CAP INCLUDED

DIMMABLE FUNCTION

Yes

CLEANING AND CARE

Vacuum to remove dust. Clean of any marks with a clean moist cloth. Always switch off the electricity supply before cleaning.



UNDER THE BELL PENDANT LAMP - US VERSION

GENERAL STANDARDS & CERTIFICATES

Conforms to UL STD. 1598 Certified to CSA STD. C22.2 NO.25O.O



LAMP RATING

 Voltage
 12OV AC

 Frequency
 6OHz

 IP Rating
 IP2O

 Socket
 1 x E26

Max. 6OW; Incandescent, Type A Max. 3OW; self-ballasted CFL Max. IIW; Self-ballasted LED

BULB RECOMMENDATION

Lamp base E26

Dimensions Ø125 X 175mm

Light source shape G125

Max wattage See rating
Light source type LED